

**REF.**

SKYL M BK/IV LED UL
SKYL M BK/GD LED UL

SKYL M IV/IV LED UL
SKYL M IV/GD LED UL

SKYL M BN/IV LED UL
SKYL M BN/GD LED UL

SKYL M GD/IV LED UL
SKYL M GD/GD LED UL

LIGHT SOURCE

120V: Dimmable

Driver:

Constant Voltage 24V

LED Integrated:

Led module

2700K / 4000K, CRI>90, 8,5W, 50-60Hz, 262 lm*

*Measurements obtained by theoretical calculations at LZF (2.700K) using ivory white shades. Veneer Ref: 20 Ivory White.

PACKAGING

Box Size: 17 × 12 × 6"

Box Volume: 0,7 ft³

Weight: Gross - 6,2 Lb | Net - 4 Lb

MATERIALS & COMPONENTS

Multimaterial Shade

Wood Veneer, Perforated Metal & Textured Glass

Metal Structure, Perforated Metal & Base

Black Electrical Cable with Dimming Switch: 57"

FINISHES**WOOD VENEER**

● 20 Ivory White

● 22 Natural Beech

PERFORATED METAL

● IV-Matt Ivory
with Wood Veneer 20

● GD-Gold
with Wood Veneer 22

METAL

*On Request

● IV-Matt Ivory

● *BN-Black Nickel

● BK-Matt Black

● *GD-Gold